ERRATA TO 2020 EDITION

Tome II

Appendix 8

Appendix 8.3 p.3 Correction of MS 1700 classification : A becomes B

RSE-M - Edition 2020 - Errata Appendix 8.3

| MS N° | Classifi- cation | TEXTS INVOLVED | MS subject | Reglementation |
|-------|---------------------|---|---|---------------------------|
| 1704 | В | M 3403, ZY 350 | Detail on the overlength of the thickness representative of the maximum thickness of the part | |
| 1703 | В | M 3304 | Clarification on sampling positions of specimens for mechanical tests | |
| 1702 | В | B 3657 | Reintroduction concerning fatigue analysis in test situations | |
| 1701 | В | Q 2300 | Withdrawal of the requirement of the presence of DR in the NSQ | |
| 1700 | ĄΒ | B 3178, B 3624.3, B 3625 | Clarification of taking account of local thermohydraulic phenomena | |
| 1699 | В | B 3231.7, B 3238.5 | Clarification of the text on the classification of the requirements for nozzles | |
| 1698 | В | Q 2300 | Change of an index in a formula | |
| 1697 | В | | Updating of standard EN 10228 | |
| 1696 | В | Q 2280 | Detail on the role of expert assessment of equipment after tests in its qualification | |
| 1695 | В | MC 3160, MC 3312 | Clarification on the possibilities of moving the cable or hole of IQI during a double wall technique | |
| 1694 | В | Z I, A 1401, A 1402, A 1502, C 2200, C 2300, D 2200, D 2300, H 2200 | Creation of STR M 3307 Bis, reference technical specification for austenitic stainless steel sheet products of levels 2 and 3 | |
| 1693 | В | F 6500, F 6600 | Section F 5000 and F 6600 brought back into consistency | |
| 1692 | В | M 4401 | Definition of prolongations for prismatic specimens, brought back to consistency with standard ISO 6892-1 2016 | |
| 1691 | В | C 3223.8 | Change of the scope of C 3222.8 (sizing of torispherical bottoms) and introduction of an analytical formula | |
| 1690 | В | F 6420 | Detail on the conditions of use of products that could contain pollutant agents | |
| 1689 | В | C 3223.6 | Extension of the scope of C 3223.6 (sizing of elliptical bottoms) | |
| 1688 | В | A1300, A 1401 | Updating of the referenced NF EN 10028-1 edition | |
| 1687 | В | A 1500, M 2312 | Detail on the sampling positions on a drilled bar before heat treatment | |
| 1686 | R | ZY 350 2.1, ZY 350 2.3 | Withdrawal of the reference to STR M 3203 (internal part without a pressure part) | Order dated 12/30/2015 |
| 1685 | В | M 4102 | Exclusion of NC 15 Fe T Nb A and NC 19 Fe Nb grades for pressure parts | |
| 1684 | В | M 3407 | English edition only - translation correction | |
| 1683 | В | A 1500, M 4107 | Detail on the samples to take for micrography | |
| 1682 | В | M 4102 | Clarification on the temperature range for the treatment to bring NC 19 Fe Nb grade into solution | |
| 1681 | В | | English edition only - translation correction | |

© AFCEN 3